

below the top edge of the lower rear panel and between the forward panel and the lower rear panel;

wherein an amount of the upper rear panel portion that is disposed below the lower rear panel top edge and between the forward and lower rear panels is adjustable to accommodate various sizes of automobile seats.

~~17~~¹³ The seat cover of claim ~~16~~¹², further comprising:
a first securing strap extending from adjacent the upper edge of the top rear panel; and
a second securing strap extending from adjacent the bottom edge of the top rear panel.

~~18~~¹⁴ The seat cover of claim ~~17~~¹³, further comprising:
a third securing strap extending from adjacent the upper edge of the top rear panel,
wherein the first and third securing straps are spaced apart from each other.

~~19~~¹⁷ The seat cover of claim ~~16~~¹², wherein the surface and forward panels are formed of an inelastic material.

~~20~~¹⁸ The seat cover of claim ~~19~~¹⁷, wherein the inelastic material is sheepskin.

~~21~~¹⁹ The seat cover of claim ~~20~~¹⁸, wherein the upper and lower rear panels are formed of an elastic material.

~~22~~²⁰ The seat cover of claim ~~16~~¹², further comprising:
means for constricting the top edge of the lower rear panel.

~~23~~²¹ The seat cover of claim ~~22~~²⁰, wherein the constricting means comprises a drawstring.

a sleeve affixed to the top edge of the rear panel, wherein the sleeve contains the drawstring.

a pocket lining extending from the bottom edge of the upper rear panel to the top edge of the lower rear panel for forming a pocket.

securing hooks attached to distal ends of the first and second securing straps.

27. The seat cover of claim 26, wherein the first and second securing straps are made of elastic material.

W

A